

Create your own AirMaster®

You can also 'Create your own AirMaster', where you have the freedom to create the colour combination of the carpet tiles yourself.

With just one click you will get insight in to how your design will look in various environments. In total **more than 6 million possibilities** are available giving you endless design freedom to create your own AirMaster. For more information: www.desso-airmaster.com.



Preliminary specification according to EN 1307

| | | |
|--|--|--------------|
| Type of manufacture | Tufted 1/10 " | ISO 2424 |
| Aspect | Structured loop pile | ISO 2424 |
| Dye method | Solution dyed | |
| Dimension | 50 cm x 50 cm / 19,68" x 19,68" (20 tiles per box) | EN ISO 24342 |
| Primary backing | Colback® Gold Polyester fleece | ISO 2424 |
| Secondary backing | DESSO EcoBase® * - Containing at least 75% C2C positively defined recycled content | ISO 2424 |
| Pile fibre composition | BCF Polyamide 6 and ECONYL® (ECONYL® is made from 100% regenerated content) ** | ISO 2424 |
| Total thickness | 6.0 mm 0.2 inch | ISO 1765 |
| Effective pile thickness | 2.4 mm 0.09 inch | ISO 1766 |
| Total mass | 4150 g/m ² 122.5 oz/yd ² | ISO 8543 |
| Total pile mass | 650 g/m ² 19.2 oz/yd ² | ISO 2424 |
| Effective pile mass | 345 g/m ² 10.2 oz/yd ² | ISO 8543 |
| Pile density | 0.144 g/cm ³ 0.0052 lb/in ³ | ISO 8543 |
| Number of tufts | 1580 /dm ² 132104 /yd ² | ISO 1763 |
| Stroll test | ≤ 2,0 kV | ISO 6356 |
| Vertical resistance | ≤ 1 x 10 ⁹ Ohm | ISO 10965 |
| Use classification | 33 Commercial - heavy use | EN 1307 |
| Dimensional stability | ≤ 0,2 % | EN 986 |
| Impact sound reduction ΔL _w | 25 dB | ISO 10140 |
| Noise reduction | 0.15 α _w | ISO 354 |
| Flammability | B _{fl} - s1 (loose laid tested) | EN 13501-1 |
| Light Reflectance Value (LRV) | See right side page per colour | BS 8493 |
| Colour Depth (L) | See right side page per colour | CIELAB |

* DESSO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle to Cradle® Certified CM Product Standard Version 3.0. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com

** ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

With EcoBase™ backing



EN 14041
 0493-CPR-0002

Manufactured by
 Tarkett BV
 PO Box 169
 NL-5240 AD
 Waalwijk

