





Specification according to EN 1307

Type of manufacture	Tufted 1/10 "	ISO 2424
Aspect	Loop pile	ISO 2424
Dye method	Solution dyed	
Dimension	50 cm x 50 cm / 19,68" x 19,68"	EN ISO 24342
	(20 tiles per box)	
Primary backing	Polyester fleece	ISO 2424
Secondary backing	DESSO ProBase Polyver®	ISO 2424
Pile fibre composition	BCF Polyamide 6	ISO 2424
Total thickness	6.5 mm 0.3 inch	ISO 1765
Effective pile thickness	3.0 mm 0.12 inch	ISO 1766
Total mass	4050 g/m² 119.5 oz/yd²	ISO 8543
Total pile mass	580 g/m² 17.1 oz/yd²	ISO 2424
Effective pile mass	360 g/m² 10.6 oz/yd²	ISO 8543
Pile density	0.120 g/cm³ 0.0043 lb/in³	ISO 8543
Number of tufts	1580 /dm² 132104 /yd²	ISO 1763
Stroll test	≤ 2,0 kV	ISO 6356
Use classification	33 Commercial - heavy use	EN 1307
Dimensional stability	≤ 0,2 %	EN 986
Impact sound reduction ΔL_w	25 dB	ISO 10140
Noise reduction	0.20 α_w	ISO 354
Flammability	B _{f1} - s1 (loose laid tested)	EN 13501-1
Light Reflectance Value (LRV)	See right side page per colour	BS 8493
Colour Depth (L)	See right side page per colour	CIELAB

With ProBase™
backing



Cradle to Cradle Certified® is a certification mark licensed by the Cradle to Cradle Products Innovation Institute.

With EcoBase™
backing



Cradle to Cradle Certified® is a certification mark licensed by the Cradle to Cradle Products Innovation Institute.




EN 14041
0493-CPR-0002

Manufactured by


Tarkett BV
PO Box 169
NL-5240 AD
Waalwijk



2033
L 48,62 / LRV 17,28




3821
L 33,68 / LRV 7,86



7071
L 48,99 / LRV 17,58



8431
L 38,76 / LRV 10,52




8901
L 24,38 / LRV 4,22



8905
L 50,13 / LRV 18,53




9092
L 29,18 / LRV 5,91




9104
L 35,52 / LRV 8,76



9107
L 43,41 / LRV 13,43



9505
L 48,36 / LRV 17,08



9513
L 32,54 / LRV 7,32



9991
L 20,85 / LRV 3,21