





Preliminary specification according to EN 1307

Type of manufacture	Tufted 1/10 "	ISO 2424
Aspect	Structured loop pile	ISO 2424
Dye method	Solution dyed	
Dimension	50 cm x 50 cm / 19,68" x 19,68"	EN ISO 24342
	(20 tiles per box)	
Primary backing	Polyester fleece	ISO 2424
Secondary backing	DESSO EcoBase® * - Containing at least 75% C2C positively defined recycled content	ISO 2424
Pile fibre composition	BCF Polyamide 6 ECONYL® (ECONYL® is made from 100% regenerated content) **	ISO 2424
Total thickness	6.0 mm 0.2 inch	ISO 1765
Effective pile thickness	2.8 mm 0.11 inch	ISO 1765
Total mass	4100 g/m² 121.0 oz/yd²	ISO 8543
Total pile mass	610 g/m² 18.0 oz/yd²	ISO 2424
Effective pile mass	355 g/m² 10.5 oz/yd²	ISO 8543
Pile density	0.127 g/cm³ 0.0046 lb/in³	ISO 8543
Number of tufts	1580 /dm² 132104/yd²	ISO 1763
Stroll test	≤ 2,0 kV	ISO 6356
Vertical resistance	≤ 1 x 10⁹ Ohm	ISO 10965
Use classification	33 Commercial - heavy use	EN 1307
Dimensional stability	≤ 0,2 %	EN 986
Impact sound reduction ΔL _w	24 dB	EN 1307
Noise reduction	0.15α _w	ISO 354
Flammability	B _{fl} - s1 (loose laid tested)	EN 13501-1
Light Reflectance Value (LRV)	See right side page per colour	BS 8493
Colour Depth (L)	See right side page per colour	CIELAB

* DESSO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle to Cradle® Certified CM Product Standard Version 3.0. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com

** ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

With EcoBase™ backing




ECONYL®
ENDLESS POSSIBILITIES




EN 14041
0493-CPR-0002

Manufactured by


Tarkett BV
PO Box 169
NL-5240 AD
Waalwijk




2015
L 45.96 / LRV 15.24




2023
L 40.62 / LRV 11.63




2102
L 33.66 / LRV 7.84



2927
L 59.44 / LRV 27.51




3913
L 38.23 / LRV 10.22




5038
L 47.33 / LRV 16.27



6022
L 47.28 / LRV 16.24




7942
L 31.33 / LRV 6.79




8832
L 34.81 / LRV 8.41



9005
L 36.88 / LRV 9.47




9055
L 46.68 / LRV 15.77




9093
L 38.41 / LRV 10.32




9097
L 50.14 / LRV 18.54




9504
L 43.96 / LRV 13.81




9508
L 58.41 / LRV 26.40



9526
L 55.73 / LRV 23.64



9950
L 45.19 / LRV 14.68



9965
L 34.25 / LRV 8.13