

# iD TILT

## TECHNICAL DATA

Certification & classification	Standards	iD Tilt
Type of floor covering	EN ISO 10582	Modular heterogeneous product with interlocking connection
CE certification	EN 14041	Yes
Classification	EN ISO 10874 (EN 685)	Commercial: 34 Industrial: 43
<b>Technical characteristics</b>		
Total thickness	EN ISO 24346	5,0 mm
Wear layer thickness	EN ISO 24340	0,70 mm
Total weight	EN ISO 23997	7400 g/m <sup>2</sup>
Wear layer binder content	EN ISO 10582	Type I
Dimensions	EN ISO 24342 - EN 427 Tiles*	91,44 x 91,44 cm (Granite) 3 tiles/box (= 2,51 m <sup>2</sup> - 18,56 kg) 45,72 x 45,72 cm (Concrete - Tarmac - Woven) 10 tiles/box (= 2,09 m <sup>2</sup> - 15,47 kg)
Surface treatment (PUR)		Yes, TopCleanXP™
<b>Technical performances</b>		
Dimensional stability	EN ISO 23999 - EN 434	< 0,15 %
Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1 over concrete substrate
Residual indentation	EN ISO 24343-1 - EN 433	< 0.10 mm
Furniture leg	ISO 16581 - EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Curl resultant to heat	ISO 23999 - EN 434	≤ 2 mm
Impact sound reduction	EN ISO 717-2	ΔL <sub>w</sub> = 6 dB
Thermal resistance	EN ISO 10456	approx. 0,05 m <sup>2</sup> K/W
Light fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893 DIN 51130	μ ≥ 0,30 DS R9
Electrical properties	EN 1815 EN 1081	< 2 kV on concrete R1 > 10 <sup>9</sup> Ω
Resistance to chemicals	EN ISO 26987 - EN 423	Resistance
<b>Environmental TAG</b>		
VOC emission	ISO 16000-9	< 100 µg/m <sup>3</sup>
Recycled content		0%
Recyclable		100%
Plasticizer		100% Phtalate-free

The above information is subject to modification for the benefit of further improvement. (01/17).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

\*The 2 formats are not interconnectable.

CUSTOMS TARIFF : 4820 5000 00



According to Classification ISO 10874

