

LINOLEUM


LINO

designed by nature



Tarkett

THE ULTIMATE
FLOORING EXPERIENCE



Tarkett's Lino is made from natural ingredients in Narni, Italy, with the same original recipe since 1898, enabling Tarkett's team to gain a real know-how and to have an intimate understanding of every natural ingredient to adapt manufacturing to the variations of each year's crop.

We constantly innovate in production processes, develop colours and new striking designs and improve our flooring technical characteristics for specific uses such as acoustic comfort in Education or Electrostatic Discharge (ESD) control.

Tarkett's Lino combines tradition and innovation to meet the needs of consumers worldwide and provide them with a unique experience.

Our linoleum offers a timeless design and a robustness that stand the test of time.



CONTENTS

Heritage	04
Natural	06
Design	10
Robust	26
Cleaning and maintenance	28
Technical solutions	30
Range overview	32
References	34
Technical data	38

HERITAGE

A TRADITIONAL FLOORING MADE IN ITALY

One of Italy's smallest regions, Umbria lies directly in the centre of Italy. Tarkett's linoleum plant began its production in Narni, Italy, at the end of 19th century, when European countries commonly used linoleum for flooring and wall-coverings. By the 1920s, there were around 100 sites making linoleum. In the early 1990s, Tarkett began to invest in the modernization of the entire production system. Today, Narni is accredited ISO 9001 and holds important environmental certifications including ISO 14001, ISO 14067, ISO 50001, OHSAS 18001, SWAN and Der Blaue Engel. Now only 4 factories - all in Europe - produce linoleum. Tarkett is a global player, exporting more than 90% of its linoleum across the world.




The Tarkett Linoleum plant at NARNI, easily recognisable by the characteristic shape of the ovens building, began its production of Linoleum at the end of the 19th century. The plant represents one of the first industries, which shaped the industrial development of Narni and the surrounding area.

Our core values

- Entrepreneurial spirit
- Operational excellence
- Deliver the ultimate flooring experience
- Positive customer attitude
- Empowerment and accountability
- Take care of the future



1929, Italy
The ball room of Conte
Grande Ship



Mindful of the environment, we made innovative improvements in our production processes to reduce our operational impact. As a result, Tarkett's Lino is a flooring solution that blends craftsmanship with the most advanced technology.

NATURAL

THE NATURAL CHOICE FOR PEOPLE AND THE ENVIRONMENT

Tarkett's Lino is made from the same original recipe since 1898 and yet it continues to be a modern, versatile and sustainable flooring, made of natural and renewable ingredients such as linseed oil, pine rosin, wood and cork flour and jute. Our Cradle to Cradle® approach ensures we design our products to positively contribute to the environment and people's well-being at each step of the product's life, while supporting the transition to a circular economy business model.

We put in place a number of initiatives to achieve our ambition of a zero-emission site at Narni. To ensure a more responsible use of natural resources, we've installed systems such as heat exchangers that recover and reuse heat from ovens, a biomass boiler that produces hot water to heat the ovens and a closed-loop water system. These have helped us establish a more sustainable manufacturing approach and minimise our impact on the environment.



GOOD MATERIALS

You care about choosing a flooring made from natural and high quality ingredients?

In making linoleum, we use materials that contribute positively to people's health and the environment. Closed-loop design starts here, so that good materials become future resources that can be reused or returned to nature as biodegradable ingredients

- **94% natural raw materials** - linseed oil, pine rosin, wood and cork flour, calcium carbonate and jute.
- **78% from abundant renewable resources** - including local suppliers.
We support local linen producers to reduce our carbon footprint.
- **100% of ingredients have been positively assessed** according to Cradle to Cradle® framework for health and environment. As such Tarkett's Lino exceeds European REACH regulation requirements.
- **100% recyclable** - Tarkett's Lino offcuts can be fully reused as raw materials for future products or packaging through our ReStart® Programme.



RESOURCE STEWARDSHIP

You want a linoleum produced in a responsible way?

Driven by the standards of our World Class Manufacturing programme for continuous improvement of processes, we reduce our operational impact and preserve the environment.

- Pioneering the new ISO14067 product carbon footprint certification, in addition to existing ISO9001 quality, ISO14001 environment, ISO50001 energy and OHSAS 18001 safety management certification.
- 100% recycled /recirculated industrial water (closed-loop).
- Rainwater collection and re-use.
- Green House Gases (GHG) emission reduction by 44% vs 2010 (the equivalent of a 23.541 km car journey).
- Producing electricity, heating and cooling power from a single device (a gas engine) to increase energy efficiency in a profitable and sustainable way (30% self-produced energy).
- Increasing renewable energy use through photovoltaic panels, a biomass boiler and a geothermal system (internal production) and the purchase of 100% renewable electricity.



NATURAL



PEOPLE-FRIENDLY SPACES

You care about the comfort and well-being of users?

We create flooring designed for improved indoor air quality that respects people's health and well-being. Tarkett's Lino enhances people's everyday sensorial experience, through colours and patterns, as well as through acoustic or underfoot comfort. All of which offer key advantages for schools, universities and hospitals.

- **Research** on how to best use colour and design to enhance aesthetics and ergonomics for stimulating, productive or restful environments.
- **Innovation** for a better sound and thermal insulation, and for improved underfoot comfort.
- **Good air quality:** VOC emissions (<100µg/m³) 10 times lower than the most stringent industry requirements.
- Naturally phthalate-free.
- Natural bactericidal qualities.
- **Hardwearing and resistant,** Tarkett's Lino xf²™ surface treatment simplifies cleaning and maintenance, which means 3.7% less water usage, 8.9% less electricity and 25% less detergent*.

*Compared to linoleum without xf2.



REUSE

You want to play a role in ensuring a sustainable future?

We recycle at every step of the linoleum life cycle to upcycle waste and avoid landfill. We believe products should no longer have an end of life, but an end of use to then become resources for new products. Join us in the transformation towards a circular economy.

- Tarkett's Lino is **100% recyclable**, from linoleum paste and surplus jute to powders.
- By recycling 1,600 tons of linoleum annually, we reduce our need for virgin raw materials.
- Our dedicated ReStart® recycling programme helps customers worldwide to collect and recycle installation offcuts.
- Our objective is **0% production waste by 2020** at Narni.



DESIGN

Natural, versatile and sustainable, combining tradition, craftsmanship and innovation, Tarkett's Lino offers a fresh approach to the flooring needs of today and lifestyles of tomorrow.

OPEN TO A WORLD OF COLOUR

Drawing on on-going trends analysis and colour expertise, our ranges have been developed through consultation with architects across the world at every design phase. It has enabled Tarkett to perfect the right combination of colour, balance and structure for each design concept, meeting the ambitions of any architectural project.


To anticipate how needs will change, our design teams explore emerging architectural, cultural and lifestyle trends. We share these insights in our Tarkett Observer studies that identify key orientations to enhance interior building design and user experience in healthcare, education and retail environments of the future.

Tarkett's Lino now comes in a complete solution that goes through the ages and is more contemporary than ever. From the floor to the wall, whether you need a compact, acoustic or conductive option, a variety of design patterns and colours opens up to you.



FLOORCRAFT AND CUSTOMISATION SERVICE

For projects looking for a more individually customised design or colour, Tarkett offers a dedicated customisation service, ready to translate your ideas into unique flooring concepts.



OUR DESIGN ORIENTATIONS

Human Inside

- Creating social cohesion for a stimulating environment that improves focus and concentration.
- An environment that plays with graphic and colour codes to give meaning to each area.

Interactive Space

- Flexible and modular design to change perceptions of learning and stimulate creativity.
- Tonic and bright colour range with materials and patterns that bring the present into the future.

Green value

- Creating a first contact with eco-responsibility and integrating environmental awareness.
- Greens, browns and neutrals and patterns that suggest nature. Re-usability and recyclability.

DESIGN - OUR RANGE

Veneto

A collection of strong and subtle marbled designs in soft or intense pattern variations for a timeless effect. All shades of the colour spectrum in a combination of neutral and contemporary accents.

Grands Classiques: a selection of 20 timeless colours amongst the Veneto that we guarantee in production until 2033. They are available in different levels of traffic resistance with xf™ surface treatment, and can be matched with our range of multicolour welding rods for a perfect finish. This includes Sicuro R10 anti-slip and Essenza non-permanent surface finish. Grands Classiques designs are also available in acoustic option: Silencio - 18dB.



Style Emme and Style Elle

A design range where the natural patterned beauty of linoleum meets modern style. It's a subtle mix between contemporary colours and light marbled surfaces.

- **STYLE EMME** a subtle marbling for refined and sophisticated styling.
- **STYLE ELLE** a discrete directional linear design.



Etrusco

A contemporary linoleum range featuring sixteen deep and radiant colours.

Thanks to its deep colours and plain design, Etrusco can be easily combined with any other type of pattern or used alone, for great design effects.



Trentino

A collection mixing modernity and tradition, Trentino offers a subtle semi-directional pattern, made of 3 colours : a main marbled colour, with two contrasting tones, giving the design depth.



Originale

The only linoleum Cradle to Cradle® Gold certified.

The real nature of Tarkett's lino: authenticity, product essence, sustainability. This new collection features 2 striking designs, Minerale and Vegetale, where vegetal pigments give authentic colours.

- **MINERALE**: a marbled soft design with a warm linoleum effect
- **VEGETALE**: a linear design close to the plant aspects, like leaf fibres.



LinoWall

The only linoleum approved for use on walls and featuring Bs2-d0 fire certification, LinoWall opens up a world of co-ordinated design possibilities. Three pastel colours have been specially chosen to complement the palette of our floor collection, while three neutral shades provide a direct match between wall and floor.



Besides its technical performances, one of the greatest strengths of Tarkett's Lino is its rich colour palette. All colours of the chromatic circle are present in the range, offering unlimited options for mix and match, and fitting every ambiance.

Our fresh, distinctive linoleum collection blends design and colour to create contemporary looks that are right on-trend, with the accessories you need for a perfect finish. The range consists of the Veneto, Style Elle, Style Emme and Etrusco designs, to which we've added two newcomers, Trentino - a subtle pattern whose two contrasting tones give the design depth - and Originale - Cradle to Cradle™ Gold level certification. And we don't stop at floor-level. Our new wall-approved LinoWall is another first, it offers co-ordinated interiors from the ground up.

All of our linoleum flooring and wall covering come with the xf² surface-treatment technology for excellent resistance and easy maintenance, ideal in heavy traffic environments. The Veneto and the Originale ranges are also available with a factory-applied, non-permanent finish called Essenza.


★ 20 Grands Classiques

Linoleum Flooring


COMPACT				
2mm xf ²	2	Veneto	14871	---
2.5mm xf ²	2.5	Veneto	14872	---
	2.5	Style Elle	14825	---
2.5mm xf ²	2.5	Style Emme	14835	---
	2.5	Etrusco	14877	---
	2.5	Trentino	14502	---
2.5mm Essenza	E	Veneto	1805	---
	E	Originale Minerale	14042	---
	E	Originale Vegetale	14032	---
3.2mm xf ²	3.2	Veneto	14873	---
3.8mm xf ²	S	Veneto Silencio	14892	---
	S	Style Elle Silencio	14783	---
	S	Style Emme Silencio	14782	---
	S	Etrusco Silencio	14894	---
	S	Trentino Silencio	14124	---
4.4mm xf ²	AC	Veneto Acoustic Cork	14881	---
SD	Linoleum Static Dissipative	14995	---	
C	Linoleum Conductive	14991	---	
R10	Veneto Sicuro	1863	---	
B ₄	Veneto B ₄	14898	---	
B ₄	Etrusco B ₄	14078	---	
B ₄	Style Emme B ₄	14088	---	
B ₄	Style Elle B ₄	14098	---	
B ₄	Trentino B ₄	14128	---	

Linoleum Wall

2mm xf ²	LinoWall	14010	---
--- Colour code * on request			



LINOLEUM xfTM





LINO 18 BROCHURE

LINOLEUM xf²



LINO 19 BROCHURE

LINOWALL

The only linoleum approved for use on walls and featuring Bs2-d0 fire certification, LinoWall xf² opens up a world of co-ordinated design possibilities.

Three pastel colours have been specially chosen to complement the palette of our floor collection, while three more neutral shades provide a direct match between wall and floor.


Our LinoWall also comes with xf² surface-treatment technology.



ORIGINALE

Originale reflects the desire for a pure, authentic look that's closer to nature. 100% natural in its composition and Cradle to Cradle™ Gold-certified, this is our most sustainable, nature-friendly linoleum flooring to date.

The range includes two new designs, both made using natural pigments derived from renewable organic sources like charcoal and walnut, and available with a factory-applied, non permanent finish called Essenza. Vegetale features a gently marbled linear design resembling plant fibres, enhanced by natural colours.





NCS S 6010-Y30R


E

NCS S 6010-Y30R


E



LINOLEUM xfTM



LINOLEUM xfTM



ROBUST

A HARD-WEARING SOLUTION OVER ITS LIFETIME

For 150 years, linoleum flooring has been appreciated for its natural beauty, comfort, durability and versatility in most interior environments. Tarkett was an early innovator in surface treatments, with the xf^{2™} technology added to its linoleum, to improve resistance and simplify maintenance for significant cost savings in daily cleaning and care.

xf^{2™} for excellent performance

xf^{2™} increases resistance for even longer durability and for a reduced maintenance, leading to a highly cost-effective flooring.

- Micro-reinforced polyurethane UV treatment seals and hardens the surface to make it more resistant to dirt and daily wear and tear.
- A smooth matt appearance prevents accumulation of dirt or stains.
- No need for polish, stripping and polymer waxing over the lifetime of the surface, providing soil barriers are correctly put in place, regular maintenance is operated (daily vacuuming and mopping), furniture appropriate leg coverings and daily surveillance.
- Excellent resistance to abrasion, stains and chemicals.

Superior resistance to abrasion

No other linoleum is so resistant to abrasion. We have conducted extensive internal and external laboratory testing to evaluate the resistance of xf^{2™} linoleum to abrasion over time. With the help of an electron microscope and 3D surface profilometer we are now able to see, magnified, the proof of the unbeatable resistance of xf^{2™}. Tests are done on Competitors A, B and Tarkett samples, before and after dry abrasion by a rotation tumbler machine equipped with black pads. All linoleum are PU UV coated, following producers declarations. After 30 minutes, the test machine began to degrade the finish of Competitors' Samples A and B. Tarkett's test continued for one hour without visible finish degradation.



Competitor A, before abrasion



Competitor B, before abrasion



Tarkett xf^{2™}, before abrasion



Competitor A, after abrasion



Competitor B, after abrasion



Tarkett xf^{2™}, after abrasion

After abrasion competitor A and B are destroyed when Tarkett xf^{2™} is still intact.



NEW improved xf^{2™} WELDING RODS

The new formula developed by Tarkett - both multi-colour and traditional uni-colour – offers a very easy installation and exceptional resistance to all kinds of soiling and abrasion for an effective cleaning.

Naturally inhibiting bacterial growth

Flooring contributes to ensuring hygienic environments in public buildings – from schools to hospitals where stain resistance to medical chemicals is mandatory for flooring materials.

Independent testing by third party prove that Tarkett's Lino has naturally bactericidal properties against the most common bacteria such as E-coli and MRSA.

Reduced life cycle cost for Linoleum xf^{2™}

The cost of the initial investment and installation normally represents just a small part of the flooring's total life cycle cost. The rest is cleaning and maintenance. As the Linoleum xf^{2™} doesn't require first surface treatment after installation, neither regular wax or polish maintenance during its lifetime, consumption of water and detergent decrease significantly and give Linoleum xf^{2™} a very favorable life cycle cost.

Compared with Linoleum flooring treated with a non-permanent acrylic finish, payback on the extra investment could come within 2 months*.

For more information, please contact your Tarkett representative.

*Case study: school of 2000m² (class rooms 1300m² and corridors 700m²), comparison between untreated Linoleum and Linoleum xf^{2™}. For 20 years life time, respecting cleaning and maintenance recommendations: entrance matting, regular cleaning and furniture appropriate leg coverings and daily surveillance.

Savings:

- 3.7% of water saved
- 25% less detergent
- 8.9% less electricity power
- 3.8% less manpower

Simplifying cleaning and maintenance

The reinforced surface of linoleum xf^{2™} means no polish, stripping and polymer waxing over the lifetime of the product, providing soil barriers are correctly put in place, regular maintenance is operated (daily vacuuming and mopping), furniture appropriate leg coverings and daily surveillance. As a result, it requires less frequent, less intense cleaning and maintenance and reduces the use of water, energy and chemical detergents for a better environmental footprint.

CLEANING AND MAINTENANCE

CLEANING AND MAINTENANCE : NO POLISH, NO WAX*

Modern day-room cleaning aims to reduce wet cleaning procedures and replace them with drier cleaning techniques, like the use of centrally laundered pre-impregnated mops and the wide application of appropriate machines. This makes work more effective and easier for the cleaning staff, and minimizes environmental impact. Less cleaning chemicals and less fresh water are used.

1 > Initial site cleaning



After installation, initial site cleaning is required: vacuum, sweep or damp mop the area to remove building dust and loose dirt. A combined scrubber/dryer with brushes or red pads cleans large areas very effectively. Use detergent with a low pH (3-5).

xfTM will not be removed by any cleaning operation.

2 > Daily and regular cleaning



Remove dust and dirt with yarn or microfiber mops or disposable mops, dry or impregnated or vacuum the floor.

Use a mop dampened with water or detergent solution to remove spots. It is essential that water does not stay on the floor or leave a film. The floor should be virtually dry after 15-20 seconds. If required spray clean the floor with a rotary machine and red pad.

3 > Periodic cleaning



or



Combined machine

Use diluted neutral detergent. Speed low 150-250 rpm or higher. Red/brown pads are usually most suitable.

Machine scrubbing + Wet vacuuming + Dry buffing

- Apply a cleaning solution (fairly strong, pH 10-11, after dilution) and allow to act for 5-10 min.
- Clean the floor using a heavy-duty single disc scrubbing machine (red pad).

Vacuum up the dirty water immediately.

- Rinse with clean water and allow the floor to dry.
- If necessary dry buff (red pad) to restore gloss.

Suitable speed: 500-1000 rpm.

Sharp edged /not maintained furniture feet, sand, pebbles, permanent push and drive movements on the same area will damage every kind of flooring over the time.

*Providing soil barriers are correctly put in place, regular maintenance is operated (daily vacuuming and mopping), furniture appropriate leg coverings and daily surveillance.

TRAINING

We provide a range of on-demand training for distributors, installers and maintenance teams on Tarkett products, installation and maintenance techniques as well as individual installation of key products for demonstration and discussion with customers.

We can deliver these worldwide in our own training facilities, such as Narni or at customer sites. Our international technical advisers can also provide personalized training or support at the start of installation on building projects.


For more information about installation training or on-site assistance in your area, contact your Tarkett representative.



TECHNICAL SOLUTIONS

SD STATIC DISSIPATIVE xf^{2™}

A safe, sustainable flooring designed for static control near computer, electronic and telecommunications equipment in medical, manufacturing, education and industry environments. Available in rolls and cuts for raised floors.



CONDUCTIVE xf^{2™} - THE ONLY CONDUCTIVE LINOLEUM

A safe and sustainable flooring designed for a stable and reliable conductive control. The natural solution for education, healthcare and office environments, especially for areas like server and computer rooms, laboratory and electronic equipment in operating theatres. Available in rolls and cuts for raised floors.

VENETO ESSENZA - 2.5mm

The traditional non-PU, factory applied, non-permanent finish, ready to walk on. Available in rolls and 608x608 mm pre-cuts for raised floors.

VENETO SICURO xf^{2™} - R10 - 2.5mm

R10 Slip-resistance rating: combines secure grip with xf^{2™}'s ease of cleaning. Ideal for building entrances. Product available on demand, in rolls and 608x608 mm pre-cuts for raised floors, in all 60 Veneto colours.

LINOLEUM B_{fl} xf^{2™} - 2.5mm

2.5 mm linoleum B_{fl} fire rating, without flame retardants. B_{fl} by its natural ingredients. Ideal for evacuation routes. Product available on demand in rolls and 608x608 mm pre-cuts for raised floors, in all designs and colours.

SILENCIO xf^{2™} - 18dB

2.5 mm linoleum with jute backing and recycled polyurethane foam underlayer, giving an excellent sound reduction of 18 dB. Available in rolls and cuts for raised floors.

VENETO ACOUSTIC CORK xf^{2™} - 15dB - 4.4 mm

2.5 mm linoleum and natural Elafono (cork underlayer) giving excellent sound reduction of 15dB. Product available on demand, in rolls and 608x608 mm pre-cuts for raised floors, in all 60 Veneto colours.

ELAFONO

2.0 mm traditional, natural, 100% natural corkment underlay installed in combination with any compact Tarkett linoleum to get added sound reduction (up to 15dB, depending on the product). Available in rolls.

Cuts 608 x 608 mm

Cuts linoleum ready for use. Designed for raised floors manufacturers, they are available in all colors, designs and technical options.




ACCESSORIES

Linoleum set-on skirtings (SOS)


- Available in: 6/8/10 cm high x 220 cm long

Linoleum set-in skirtings (SIS)

- Available in: 6/8/10 cm high x 240 cm long
- SIS outer corner available in: 6/8/10 cm high x 10 cm width (size of the corner 13x13 cm)



Lino SOS



Lino SIS



Lino SIS outer angle

SPORT APPLICATION

Tarkett's Lino is also suitable for sport application. Have a look at our selection of the Linosport range at www.tarkett-sports.com

DISCLAIMER ON YELLOWING EFFECT

Once unpacked and as a result of the natural production process, linoleum sometimes comes with a slightly yellow surface film. The yellow tint will disappear progressively with exposure to light; 24 hour exposure to bright daylight will make it disappear completely.

The phenomenon is reversible and the yellow film might reappear in areas covered by furniture or other objects. It will of course disappear again once exposed to daylight.

RANGE OVERVIEW

Colour name	Ref	Veneto 2,0 mm x f ²	Veneto 2,5 mm x f ²	Veneto 3,2 mm x f ²	Veneto Silencio 2,5 mm (acrylic) 3,8 mm	Veneto Essenza 2,5 mm (acrylic)	Veneto x f ² Bi 2,5 mm ON REQUEST	Veneto Acoustic Cork x f ² 15dB 4,4 mm ON REQUEST	Veneto Silcuro x f ² R10,2,5 mm ON REQUEST	NCS code LINOLEUM	RAL code LINOLEUM	Uni Color Welding Rod 4 mm (for compact linoleum)	Uni Color Welding Rod 4,4 mm (for acoustic linoleum)	Multicolor Welding rod (for Grands Classiques)	NCS code Multicolor Welding Rod	L	LRV	LRV of a surface* (x f ²)		
Durango	121	14872121			14898121	14881121	1863121	S3010-Y30R	1001	1751121	S3010-Y10R					67,11	37%			
100% linen	400	14872400		14892400 see ORIGINALE	14898400	14881400	1863400	S4020-Y30R	1011	1751400	14051400	S4020-Y30R				46,98	16%			
Fossil	502	14871502	14872502		14898502	14881502	1863502	S4010-Y10R	7032	1751502	S5010-Y10R					56,52	24%			
Tiger eye	524	14872524			14898524	14881524	1863524	S7020-Y40R	8008	1751524	S7010-Y30R					41,09	12%			
Ivory	601	14872601	14872604	14892604	1805604	14898604	14881604	1863604	S5502-Y	7030	1751205	14051205	S6005-G80Y	14000604	S5502-Y	50,3	19%			
*Pebble	604	14871604	14872604	14892608	1805608	14898608	14881608	1863608	S6005-G80Y	7003	1751608	14051608	S6005-G80Y	14000608	S6005-G80Y	45,7	15%			
*Smoke	608	14871608	14872608																	
*Charcoal	610	14871610	14872610		1805610	14898610	14881610	1863610	S8000-N	7021	1751098	S8002-B	14000610	S8002-B	33,8	8%				
*Sisal	611	14871611	14872611	14873611	1805611	14898611	14881611	1863611	S2020-Y20R	1001	1751611	2020-Y30R	14000611	S2020-Y20R	70,3	41%				
*Corn	612	14872612	14873612		1805612	14898612	14881612	1863612	S2040-Y10R		1751219	S2050-Y	14000612	S2040-Y10R	73,8	46%				
Coral	615	14872615			14898615	14881615	1863615	S2030-Y40R		1751615	S2020-Y30R					69	39%			
*Camel	616	14872616			1805616	14898616	14881616	1863616	S1020-Y30R		1751631	S3020-Y30R	14000616	S2020-Y20R	71,2	42%				
Eggshell	619	14872619		14892619	1805619	14898619	14881619	1863619	S1020-Y20R		1751619	S2020-Y10R				76,8	51%			
Sand	622	14872622			14898622	14881622	1863622	S2010-Y10R	1015	1751611	2020-Y30R					73,11	45%			
Azurite	624	14872624		14892624	14898624	14881624	1863624	S1515-Y20R	1014	1751619	14051619	S2020-Y10R				71,87	43%			
Silk	625	14871625	14872625	14892625	14898625	14881625	1863625	S3010-Y30R		1751625	14051625	S3010-Y				62,7	31%			
Sunflower	628	14872628		14892628	1805628	14898628	14881628	1863628	S1070-Y20R	1037	1751636	14051636	S2060-Y30R				67,3	37%		
Citrine	631	14872631			14898631	14881631	1863631	S2030-Y30R		1751631	S3020-Y30R					61,12	29%			
Chocolate	632	14872632		14892632	14898632	14881632	1863632	S7005-Y80R	8025	1751632	14051632	S7005-Y80R				35,1	9%			
Copper	634	14872634		14892634	14898634	14881634	1863634	S2040-Y40R		1751636	14051636	S2060-Y30R				63,3	32%			
*Amber	636	14872636	14873636		1805636	14898636	14881636	1863636	S2050-Y40R		1751636	S2060-Y30R	14000636	S2050-Y40R	58,35	26%				
Almond	637	14871637	14872637		14898637	14881637	1863637	S3005-Y50R	1001	1751211	S3010-Y10R					67,35	37%			
*Terracotta	641	14872641	14873641	14892641	1805641	14898641	14881641	1863641	S2070-Y80R	2001	1751641	14051641	S3060-Y70R	14000641	S3060-Y70R	45,04	15%			
Salmon	642	14872642			14898642	14881642	1863642	S2050-Y60R	3022	1751642	S2040-Y60R					62,74	31%			
Carmine	645	14872645		14892645	1805650	14898645	14881645	1863645	S1580-Y90R	3020	1751645	14051645	S2070-Y90R				42	13%		
*Grass	650	14872650			14898650	14881650	1863650	S4040-G30Y	6017	1751650	S3050-G20Y	14000650	S2060-G30Y	45,48	15%					
Mint	651	14872651			14898651	14881651	1863651	S3040-B40G		1751651	S3040-B40G					41,41	12%			
*Horizon	663	14871663	14872663	14873663	1805663	14898663	14881663	1863663	S4010-R90B		1751660	S4005-R80B	14000663	S4010-R90B	59,73	28%				
Ocean	665	14872665			1805665	14898665	14881665	1863665	S5030-R90B	5023	1751665	S5030-R90B					45,1	15%		
Lavender	670	14872670			1805670	14898670	14881670	1863670	S4020-R90B	5014	1751670	S4020-R80B					50,96	19%		
*Zinc	671	14871671	14872671	14892671	1805671	14898671	14881671	1863671	S4502-Y	7040	1751671	14051671	S4502-G	14000671	S4500-N	61,06	29%			
*Aluminium	672	14871672	14872672		1805672	14898672	14881672	1863672	S4502-G		1751672	S4502-G	14000672	S4502-G	57,74	26%				
*Steel	673	14871673	14872673	14892673	1805673	14898673	14881673	1863673	S6005-B20G	14000673	1751673	S6005-B20G	14000673	S6000-N	50,2	19%				
*Slate	674	14872674	14873674	14892674	1805674	14898674	14881674	1863674	S8502-B	9004	1751098	14051098	S8502-B	14000674	S8502-B	29,84	6%			
*Cork	679	14871679	14872679		1805679	14898679	14881679	1863679	S2020-Y20R		1751611	2020-Y30R	14000679	S2030-Y30R	69,52	40%				
Platinum	684	14872684		14892684	14898684	14881684	1863684	S2502-Y	7044	1751793	S3005-G80Y					70,18	41%			
Pewter	685	14872685		14892685	14898685	14881685	1863685	S4000-N		1751685	S4050-B					62,63	31%			
Concrete	686	14872686		14892686	14898686	14881686	1863686	S6005-R80B	7046	1751686	S6005-B20G					44,8	14%			
Navy	688	14872688			14898688	1488														

REFERENCES



Veldhoen Gilde, Venray, The Netherlands
6000m² Veneto xf™ 2,0mm, 2,5mm and 3,2mm, 2009





Day Nursery, Eckbolsheim, France
Cabinet DWPA, 800m² Etrusco xf™ 2,5mm, 2011



Sint-Ludgartis School, Merkesm, Belgium
Wollaert, 840 m² Veneto xf™ 2,5mm, 2010

TECHNICAL DATA

CERTIFICATION & CLASSIFICATION	STANDARDS	Veneto xf™ 2 mm	Veneto xf™ Style Emmie xf™ Style Elle xf™ Trentino xf™	Linoleum Bn 2.5 mm	Originale Essenza Veneto Essenza 2.5mm	Veneto Sicuro xf™ R10 2.5 mm	Etruso xf™ 2.5 mm	Linoleum Conductive xf™ 2.5 mm	Linoleum SD Static Dissipative xf™ 2.5 mm	Veneto xf™ 3.2 mm
ISO 24011 (EN 548)			One single layer calendered linoleum on jute backing.			Conductive linoleum flooring	Static Dissipative linoleum flooring	One single layer calendered linoleum on jute backing		
Type of floor covering	EN 686	-	-	-	-	-	-	-	-	-
EN 687	-	-	-	-	-	-	-	-	-	-
CE certification	EN 14041	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Classification	EN ISO 10874 Domestic Commercial Light industrial	Classes: 23 32 41	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 34 43	Classes: 23 34 43
TECHNICAL CHARACTERISTICS	STANDARDS									
Surface treatment	xf™	xf™	xf™	Essenza	xf™	xf™	xf™	xf™	xf™	xf™
Total thickness	EN ISO 24346	2.0 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm	3.2 mm
Total weight	EN ISO 23997	ca. 2 400 g/m²	ca. 3 000 g/m²	ca. 3 200 g/m²	ca. 3 000 g/m²	ca. 3 000 g/m²	ca. 3 000 g/m²	ca. 3 000 g/m²	ca. 3 000 g/m²	ca. 3 900 g/m²
Residual indentation	EN ISO 24343-1 Standard requirements Best measured value	≤ 0.15 mm ca. 0.07 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.08 mm	≤ 0.15 mm ca. 0.10 mm	≤ 0.15 mm ca. 0.10 mm
Flexibility	EN ISO 24344 Method A	≤ 25 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 40 mm Ø
Form of delivery	EN ISO 24341	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m	≤ 32 x 2 m
TECHNICAL PERFORMANCES	STANDARDS									
Fire classification	EN 13501-1	Cfl s1	Cfl s1	Bfl s1	Cfl s1	Cfl s1	Cfl s1	Cfl s1	Cfl s1	Cfl s1
Fire effluent toxicity	ISO 5659-2 (evaluation according to EN 45545-2 Annex C)	-	-	-	-	-	-	-	-	-
Impact sound reduction	EN ISO 10140-3 / EN ISO 717-2	5 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	6 dB	8 dB
Impact sound in the room	NF S31-074	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class C < 85 dB	Class B < 75 dB	
Impact sound reduction with Elafono*	EN ISO 10140-3 EN ISO 717-2	14 dB	14 dB	14 dB	14 dB	14 dB	14 dB	Not applicable	Not applicable	15 dB
Castor chair	EN ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)								
Static electrical propensity	EN 1815	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV
Electrical resistance	EN 1081	-	-	-	-	-	R1 ≤ 10 ⁸	R1 ≤ 10 ⁸	-	-
ESD-approval SP method 2472	-	-	-	-	-	-	R2 ≤ 10 ⁸	R2 ≤ 10 ⁸	-	-
EN/IEC 61340-4-	-	-	-	-	-	-	R ≤ 10 ⁸	1x10 ⁸ < R < 1x10 ⁸	-	-
Impact resistance	EN 259-2	-	-	-	-	-	-	-	-	-
Slip resistance	EN 13893 DIN 51130	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R10	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9	DS: ≥ 0.30 R9
Chemical resistance	EN ISO 26987	Resistant to dilute acids, oils, fats, current solvents and alkalis								
Thermal resistance Underfloor heating	EN ISO 10456	0.012 m ² K/W Suitable	0.015 m ² K/W Suitable	0.015 m ² K/W Suitable	0.015 m ² K/W Suitable	0.015 m ² K/W Suitable	0.015 m ² K/W Suitable	0.015 m ² K/W Suitable	0.015 m ² K/W Suitable	0.019 m ² K/W Suitable
Light fastness	EN ISO 105-B02	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
Presence of phthalate compounds	CEN ISO/TS 16181	-	-	-	-	-	-	-	-	-
Odor test requirement of emission class M1	EN ISO 16000-28 i.A., VDI 4302	-	-	-	-	-	-	-	-	-
Spongeability, washability and extra washability	EN 12956 EN 233	-	-	-	-	-	-	-	-	-
Determination of antibacterial activity	ISO 22196	Naturally bactericidal (Bacteria mix - EColi and MRSA)								
Colours	19	60 (Veneto) 13 (Style Emmie) 7 (Style Elle) 10 (Trentino)	ON REQUEST: 60 (Veneto B) 13 (Style Emmie B) 7 (Style Elle B) 16 (Etruso B) 10 (Trentino B)	29 (Veneto) 3 (Originale Vegetale) 7 (Style Elle B) 3 (Originale Minerale)	ON REQUEST: 60 (Veneto)	16	1	3	9	



SUSTAINABILITY

Tarkett was the first linoleum flooring manufacturer to be Cradle to Cradle® certified - underlining our strong commitment to sustainability.

Product certifications



Originale and Veneto Essenza 100% linen

All our linoleum ranges (except Silencio 18dB linoleum, SD Static Dissipative xf™ and Linoleum Conductive xf™ ranges)

Silencio 18dB

International certifications



*Information sur le niveau d'émission de substances volatiles dans l'air extérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Factory certifications



All our linoleum products are eligible for LEED v4 credits. For more information: <http://www.c2ccertified.org/products/registry>

The above information is subject to modification for the benefit of further improvement. (02/17).

DISCLAIMER: Although the utmost care is taken, the data here given could differ and be subject to modifications from a technical point of view. In its strive to improve its floor solutions, Tarkett reserves the right to modify its technical specifications, colours and materials at any moment and without prior notice. Please, check the effective availability of the products presented at the time of order. Due to the technical limits of reproduction and printing techniques used, the appearance (colour) of the product may vary from the samples, panels or other visual display materials exhibited to the customer. It is mandatory to have the products installed properly if they are to service correctly and safely. Refer to Tarkett technical installation and maintenance directions, available at www.tarkett.com or at your Tarkett dealer.

*Elafono : 2,0mm traditional, 100% natural cork underlay to be installed in combination with any compact Tarkett linoleum to get additional sound reduction (up to 15dB, depending on the product). Available in rolls ≤ 32 x 2m.

■ **WESTERN EUROPE:** **Austria:** Tarkett Holding GmbH, Niederlassung Wien – Tel. +43 1 47 88 062 ■ **Belgium:** Tarkett Belux Srl – Tel. +32 16 35 98 80 ■ **Denmark:** Tarkett A/S – Tel. +45 43 90 60 11 ■ **Finland:** Tarkett Oy – Tel. +358 9 4257 9000 ■ **France:** Tarkett SAS – Tel. +33 1 41 20 42 49 ■ **Germany:** Tarkett Holding GmbH, Bereich Objekt – Tel. +49 62 33 810 ■ **Greece:** Tarkett Monoprosopi Ltd – Tel. +30 210 6745 340 ■ **Italy:** Tarkett S.p.A. – Tel. +39 0744 7551 ■ **Luxembourg:** Tarkett GDL SA – Tel. +352 949 211 8804 ■ **Netherlands:** Tarkett Holding GmbH, Vestiging Nederland – Tel. +31 416 685 491 ■ **Norway:** Tarkett AS – Tel. +47 32 20 92 00 ■ **Portugal:** Tarkett SA – Tel. +351 21 427 64 20 ■ **Spain:** Tarkett Floors S.L. – Tel. +34 91 358 00 35 ■ **Sweden:** Tarkett Sverige AB – Tel. +46 771 25 19 00 ■ **Switzerland:** Tarkett Holding GmbH, Bereich Objekt Schweiz – Tel. +41 043 233 79 24 ■ **Turkey:** Tarkett Aspen – Tel. +90 212 213 65 80 ■ **United Kingdom:** Tarkett Ltd – Tel. +44 (0) 1622 854 040 ■ **EASTERN EUROPE:** **Baltic Countries:** Tarkett Baltics: Tel. +370 37 262 220 ■ **Czech Republic:** Tarkett France SAS, org. slozka – Tel. +420-271 001 602 ■ **Hungary:** Tarkett France SAS – Tel. +36 1 437 8150 ■ **Poland:** Tarkett Polska Sp. z o. o. – Tel. +48 22 16 09 231 ■ **Russian Federation:** ZAO Tarkett RUS – Tel. +7 495 775 3737 ■ **Slovakia:** Tarkett France SAS, org. zlozka – Tel. +421 248 291 317 ■ **South East Europe:** Tarkett SEE – Tel. +381 21 7557 649 (44) 569 12 21 ■ **Ukraine:** Tarkett UA – Tel: +38 (0) 44 569 12 21 ■ **ASIA AND OCEANIA:** **Australia:** Tarkett Australia Pty Ltd – Tel. +61 2 88 53 12 00 ■ **China:** Tarkett Floor Covering (Shanghai) Co. Ltd. – Tel. +86 (21) 60 95 68 38 ext 841 ■ **North East Asia:** Tarkett Hong Kong Limited – Tel. +852 2511 8716 ■ **India:** Tarkett France (India Branch) – Tel. +91 11 4352 4073 ■ **South East Asia:** Tarkett Flooring Singapore Pte. Ltd. – Tel. +65 6346 1585 ■ **AFRICA:** **Tarkett International:** Tel. +33 1 41 20 41 01 ■ **MIDDLE EAST:** **Tarkett Middle East:** Tel. +961 1 51 3363/4 ■ **Israel:** Tarkett International: Tel. +33 1 41 20 41 01 ■ **NORTH AMERICA:** **USA:** Tarkett Inc. – Tel. +1 713 869 5811 / Johnsonite – Tel. +1 440 543 8916 ■ **Canada:** Tarkett Inc. – Tel. +1 450 293 173 ■ **LATIN AMERICA:** **Brazil:** Tarkett – Tel. 55 12 3954 7108 ■ **Argentina - Chile - Uruguay:** Tarkett Latam Mercosur – Tel. +54 11 47 08 07 72 / +54 9 11 44 46 88 82 ■ **Bolivia - Colombia - Ecuador - Panama - Paraguay - Peru - Trinidad and Tobago - Venezuela:** Tarkett – Tel. +55 11 9 8410 9310 / +55 11 9 8410 0069 ■ **Mexico / Central America:** Tarkett Latam Mexico – Tel. +55 11 9 8410 9310

CUSTOMS TARIFF : 482050000000F



www.professionals.tarkett.com