DESSO Revestimiento textil - Baldosas & Listones

Fields EcoBase

Especificación según EN 1307

Fabrication	ISO 2424		Tuftado 1/10 “					
Aspecto	ISO 2424		Bucle estructurado					
Método de tintada			Tintado en masa					
Tamaño de baldosas	EN ISO 24342	cm x cm	50x50 & 100x25 / 19,68”x19,68” & 39,36”x9,84” (20 baldosas / 20 listones por caja)					
Soporto primario	ISO 2424		Vellón de poliéster					
Soporto secundario	ISO 2424		EcoBase*					
Tipo de fibra	ISO 2424		BCF Poliamida 6 ECONYL®**					
Altura total	ISO 1765	mm	6.5	inch	0.3			
Altura de fibra	ISO 1766	mm	2.8	inch	0.11			
Peso total	ISO 8543	g/m²	4100	oz/yd²	121.0			
Peso de fibra total	ISO 2424	g/m²	730	oz/yd²	21.5			
Peso de fibra en superficie	ISO 8543	g/m²	415	oz/yd²	12.2			
Densidad de fibra	ISO 8543	g/cm³	0.148	lb/in³	0.0054			
Puntadas	ISO 1763	/dm²	1580	/yd²	132104			
Carga electrostática	ISO 6356	kV	≤ 2,0					
Resistencia vertical	ISO 10965	Ohm	≤ 1 x 10^9 (sólo para baldosas de 50x50)					
Resistencia horizontal	ISO 10965	Ohm	-					
Clasificación para uso	EN 1307		33 Comercial - uso intenso					
Clase de lujo	EN 1307		LC 2					
Estabilidad dimensional	EN 986	%	≤ 0,2					
Aislamiento del sonido de impacto ΔL_W	ISO 10140	dB	23					
Absorción del sonido	ISO 354	Freq. Hz	125	250	500	1000	2000	4000
		α_s	0.01	0.03	0.06	0.15	0.26	0.31
Reducción del sonido	ISO 354	α_w	0.15					
Resistencia térmica	ISO 8302	m².K/W	0.071					
Inflamabilidad	EN 13501-1		Bfl - s1 (suelta a prueba)					
Prodis - GUT	www.pro-dis.info		5AFD3F4F					

CE

EN 14041
0493-CPR-0002

Manufactured by:

Tarkett BV
Taxandriaweg 15
NL - 5142 PA Waalwijk

Bfl-s1 DS

ECONYL® ENDLESS POSSIBILITIES

Quality- and Environmental Management System Certification ISO 9001 & ISO 14001

*EcoBase - 100% recyclable, contains up to 91% recycled and bio-based content. Recycled content is externally verified by Lloyds Register.
**ECONYL® is made from 100% regenerated content.

DESSO flooring products are to be installed in full accordance with Tarkett’s installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20240530

Tarkett BV
Taxandriaweg 15
NL-5142 PA Waalwijk

Tarkett