

# Primo SD

## Datasheet

| Classification                                       | Norm                                                                    | Tarkett Value                                                                    |
|------------------------------------------------------|-------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| Product type                                         | ISO 10581                                                               | Static dissipative pressed homogeneous vinyl flooring                            |
| Binder content                                       | ISO 10581                                                               | Type I                                                                           |
| Commercial classification                            | ISO 10874                                                               | 34 Very Heavy                                                                    |
| Industrial classification                            | ISO 10874                                                               | 43 Heavy                                                                         |
| Technical Characteristics                            | Norm                                                                    | Tarkett Value                                                                    |
| Surface treatment                                    |                                                                         | PUR Reinforced                                                                   |
| Total thickness                                      | ISO 24346                                                               | 2 mm                                                                             |
| Wear layer thickness                                 | ISO 24340                                                               | 2 mm                                                                             |
| Total weight                                         | ISO 23997                                                               | 3000 g/m <sup>2</sup>                                                            |
| Performance for CE Marking                           | Norm                                                                    | Tarkett Value                                                                    |
| Declaration of Performance #                         | EN 14041                                                                | 0019-0047-DoP-2014-03                                                            |
| Reaction to fire                                     | EN 13501-1                                                              | Bfl-s1                                                                           |
| Reaction to fire                                     | EN ISO 9239-1                                                           | ≥ 8 kW/m <sup>2</sup>                                                            |
| Reaction to fire - EN ISO 11925-2                    | EN ISO 11925-2                                                          | Pass                                                                             |
| Static Electrical Propensity                         | EN 1815                                                                 | Antistatic (≤ 2 kV)                                                              |
| Thermal resistance                                   | EN 12667                                                                | ~0,010 m <sup>2</sup> •K/W                                                       |
| Slip resistance                                      | EN 13893                                                                | Class DS (μ ≥ 0,30)                                                              |
| Technical Performance                                | Norm                                                                    | Tarkett Value                                                                    |
| Residual indentation                                 | EN ISO 24343-1                                                          | Required value: ≤ 0,10 mm<br>Best measured value: 0,03 mm                        |
| Slip resistance                                      | DIN 51130                                                               | R9                                                                               |
| Slip Resistance                                      | BS 7976-2                                                               | Low risk of slip                                                                 |
| Electrical Insulation                                | VDE0100, Part 600                                                       | Ri ≥ 5x10 <sup>4</sup> Ohms                                                      |
| Electrical resistance                                | ESD-approval SP method 2472                                             | R ≤ 10 <sup>6</sup> Ohms                                                         |
| Electrical Resistance                                | EN/IEC 61340-4-1, 100 V                                                 | R ≤ 10 <sup>6</sup> Ohms                                                         |
| Curl resultant to heat                               | EN ISO 23999                                                            | ≤ 8 mm for rolls<br>≤ 2 mm for tiles                                             |
| Castor chair                                         | ISO 4918                                                                | Suitable                                                                         |
| Colour fastness to light                             | ISO 105-B02                                                             | ≥ 6                                                                              |
| Dimensional stability                                | EN ISO 23999                                                            | Average Measured Value : ≤ 0.40 %<br>Average measured value : ≤ 0.25 % for tiles |
| Ease of Decontamination                              | ISO 8690 - DIN 25415                                                    | Excellent                                                                        |
| Chemical resistance                                  | ISO 26987                                                               | Good resistance                                                                  |
| Bacteria Resistance                                  | ISO 846 Part C                                                          | Does not promote growth                                                          |
| Underfloor heating                                   |                                                                         | Suitable (subfloor temperature maximum 27°C)                                     |
| Seam Strength Average Value                          | EN 684                                                                  | ≥ 240 N/50mm                                                                     |
| Seam Strength Individual Value                       | EN 684                                                                  | ≥ 180 N/50mm                                                                     |
| Sustainability performances                          | Norm                                                                    | Tarkett Value                                                                    |
| Recyclability through ReStart®                       |                                                                         | Recyclable                                                                       |
| Recycled content                                     |                                                                         | 25,5 %                                                                           |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) |                                                                         | 5,71 kg CO <sub>2</sub> eq /m <sup>2</sup>                                       |
| Total VOC Emissions                                  | EN 16516                                                                | Platinum (≤ 10 µg/m <sup>3</sup> )                                               |
| Formaldehyde emission                                |                                                                         | E1                                                                               |
| Dimensions and designs                               |                                                                         |                                                                                  |
| Roll                                                 | Roll 2 x 23 m                                                           |                                                                                  |
| Tile                                                 | Tile 610 x 610 mm - 16 tiles=5,95 m <sup>2</sup> /box - 40 boxes/pallet |                                                                                  |
| Number of designs available                          | 8                                                                       |                                                                                  |



The above information is subject to modification for the benefit of further improvement (06/04/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.