

Tapiflex Tiles 50

Datasheet

Classification	Norm	Tarkett Value
Product type	EN 651	Polyvinyl chloride floor coverings with foam layer
Commercial classification	ISO 10874	33 Heavy
Wear group	EN 651	T
Technical Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	3,30 mm
Wear layer thickness	ISO 24340	0,50 mm
Total weight	ISO 23997	3212 g/m ²
Surface treatment		Top Clean XP
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0120-0061-DoP-2014-05
Reaction to fire on fibreceement substrate	EN ISO 13501-1	Bfl-s1
Reaction to fire on woodchip substrate	EN ISO 13501-1	Cfl-s1
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN ISO 10456	0,04 m ² •K/W
Slip resistance	EN 13893	Class DS ($\mu \geq 0,30$)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	Required value: $\leq 0,20$ mm Best measured value: 0,10 mm Average measured value: 0,12 mm
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.10 %
Impact sound reduction - ΔL_w	EN ISO 717/2	19 dB
Reduction of in-room impact noise	NF S31-074	Class A (≤ 65 dB)
Slip resistance	DIN 51130	R9 R10
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Curl resultant to heat	EN ISO 23999	$\leq 2 $ mm
Colour fastness to light	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Recycled content		29 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		9,30 kg CO ₂ eq /m ²
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m ³)
Dimensions and designs		
Plank	Plank 250 x 1000 mm - 20 planks=5 m ² /box - 40 boxes/pallet	
Tile	Tile 50 x 50 cm / 19,68" x 19,68" - 20 tiles=5 m ² /box - 32 boxes/pallet	
Number of designs available	23	

Slip resistance : R10 only for Citizen Oak designs



The above information is subject to modification for the benefit of further improvement (09/12/2022). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.