Omnisports Compact (2.0 mm)



SUSTAINABILITY ATTRIBUTES

Circular Economy and Climate Change





Good Materials





Indoor Air Quality








This product's installation waste is recyclable in our recycling centres LCA Information above is based on the product's Environmental Product Declaration (EPD) EPD Number : S-P-01507 EPD comparison should be conducted by experts only

LIFE CYCLE ASSESSMENT



TOTAL CARBON FOOTPRINT 14,58 kg CO₂eq /m²

Product life span = 20 years



CONTRIBUTION TO GREEN BUILDING CERTIFICATIONS

BREEAM INTERNATIONAL NEW CO	DNSTRUCTION 2016	BREEAM
CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
HEA 01 - Visual Comfort	Best practices in daylighting and artificial lighting design No specific requirement at product level	VISUAL COMFORT
HEA 02 - Indoor Air Quality	TVOC at 28 days ≤ 1000 μg/m3 and Formaldehyde at 28 days ≤ 60 μg/m3	Soptimation Sopt
MAT 01 - Life Cycle Impacts	EPDs available	EPD®
MAT 03 - Responsible Sourcing of Construction Products	ISO 14001 certified	Tarkett ISO 14001 PURCHARE A MAGGARE POTTO
MAT 06 - Material Efficiency	Ingredients verified by a third party or Product composed of recycled content	MHS IN STOTEMENT
WST 01 - Waste Management	Avoid sending waste to landfill No specific requirement at product level	RECYCLABLE Ready



EED v4.1 Building Design and Construction		USCBC .
CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
MR - Environmental Product Declarations	EPDs available	EPD [®]
MR - Sourcing of Raw Materials	Signatory of the UN Global Compact or Product composed of recycled content or Recyclable at end-of-life or Bio-sourced materials	WE SUPPORT
MR - Material Ingredients	Ingredients verified by a third party or- Cradle to Cradle® certification at bronze level or higher	
MR - Construction and Demolition Waste Management	Avoid sending waste to landfill No specific requirement at product level	RECYCLABLE Ready
EQ - Low Emitting Materials and Indoor Air Quality Assessment	TVOC at 28 days ≤ 1000 μg/m3 and Formaldehyde at 28 days ≤ 10 μg/m3 Decrease the concentration of particles in the air	STO upum, oprimal indoor Air Quality Low Formissions
EQ - Interior Lighting and Daylight	Best practices in daylighting and artificial lighting design No specific requirement at product level	VISUAL COMFORT



SU SU SU

NELL BUILDING STANDARD v2		WELL	THAT IS A STATE OF
CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE	
L02 - Visual Lighting Design and L 06 - Daylight Simulation	Best practices in daylighthing andartificial lighting design No specific requirement at product level	VISUA COMFO	> 7 AL DRT
S07 - Impact Noise Management	Best practices in impact noise reduction- No specific requirement at product level		DISE N
X01, X02 and X05 - Material Restrictions, Interior Hazardous Materials Management and Enhanced Material Restrictions	Asbestos < 1000 ppm Halogenated flame retardants < 100 ppm PFAS < 100 ppm Lead < 100 ppm Cadmium < 100 ppm Mercury < 100 ppm Orthophthalates < 100 ppm <i>Higher amounts are allowed if required by</i> <i>local code</i>	Verify compliance according to chemi displayed in MHS. Evaluation threshold at le 100 ppm (0.01%) of the final proc	least
X06 - VOC Restrictions	TVOC at 28 days ≤ 1000 μg/m3 and Formaldehyde at 28 days ≤ 124 μg/m3 (E1)	STDUrg/m OPTIMAL INDOOR AIR QUALITY OPTIMAL INDOOR COMPANY LOW FORMALDEHYDE EMISSIONS	1 Namu Manaka Manaka Le Biotolia Le Biotolia Ana Amazana)
X07 - Materials Transparency	Ingredients verified by a third party or Cradle to Cradle® certification at bronze level or higher		BY DEA
X08 - Materials Optimization	Ingredients verified by a third party or Cradle to Cradle® certification at silver level or higher) er dega Itement

SKA RATING OFFICES 1.2

SKArating[®]

CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
Soft flooring	Recycled content > 50% or Renewable or natural content > 50% or Cradle to Cradle® certification at silver level or higher or EPDs available	EPD®
Reduce floor finishes sent to landfill	Avoid sending waste to landfill No specific requirement at product level	RECYCLABLE
Low VOC finishes	TVOC at 28 days ≤ 100 μg/m3 and Formaldehyde at 28 days ≤ 10 μg/m3 or Ingredient disclosure	STOLIGY''''''''''''''''''''''''''''''''''''
Daylighting	Best practices in daylighting design No specific requirement at product level	VISUAL COMFORT



DGNB System - New buildings Version 2020 International

CERTIFICATION REQUIREMENTS THE TARKETT RESPONSE **CERTIFICATION CRITERIA** EPD ENV1.1 - Building Life Cycle EPDs available Assessment Textile flooring - Quality level 4 TVOC at 28 days $\leq 100 \ \mu g/m3$ SVHC < 0,1% voc Biocidal products only in accordance with 528/2012/EC Resilient flooring - Quality level 4 ENV1.2 - Local Environment Impact TVOC at 28 days ≤ 300 µg/m3 Verify compliance according to chemicals displayed in MHS. Evaluation threshold at least SVHC < 0,1% Chlorinated paraffins < 0,1% 100 ppm (0.01%) of the final product. Manufacturer declaration may also be provided - contact TARKETT's sales representative. Phthalates that are toxic to reproduction < 0,1% No use of lead and cadmium compounds ENV1.3 - Sustainable Resource Product composed of open-loop Extraction or post-consumer recycled content voc Indoor air quality measurement after ≤10µg/m³ OPTIMAL INDOOR AIR QUALITY SOC1.2 - Indoor Air Quality construction work :10µg LOW FOR DEHYDE No specific requirement at product level Best practices in impact noise reduction-SOC1.3 - Acoustic Comfort No specific requirement at product level 2dB REDUCTION \bigcirc Best practices in daylighting and artificial SOC1.4 - Visual Comfort lighting design VISUAL COMEORT No specific requirement at product level Verifiable results in reduced life cycle TEC1.5 - Ease of Cleaning Building 0% costs for cleaning EASY CLEANING Components No specific requirement at product level TEC1.6 - Ease of Recovering and Efficient use of resources Recycling



DGNB

HQE BÂTIMENT DURABLE v4



CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE	
Qualité de l'air intérieur	Mesure de polluants dans l'air après travaux	CopTIMA INDOOR AIR QUALITY COMMALDEHYDE	
Confort Visuel	Bonnes pratiques sur l'éclairage naturel et artificiel Pas d'exigence spécifique au niveau des produits		VISUAL COMFORT
Déchets	Enviter l'envoi à la décharge Pas d'exigence spécifique au niveau des produits	RECYCLABLE	Ready
ACV	Calcul des impacts envrionnementaux de l'opération selon la RE2020		FDES
Economie locale	Composant issu d'une filière de valorisation matière des déchets		32% RECYCLED CONTENT

greenstar

Green Star - Interiors v1.3			greenstar
CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE	
Indoor Pollutants	TVOC at 28 days ≤ 1000 μg/m3 and Formaldehyde at 28 days ≤ 10 μg/m3	S10µg/m OPTIMAL INDOOR AIR QUALITY	<10µg/m ³ LOW FORMALDEHYDE EMISSIONS
Lighting and Visual Comfort	Best practices in daylighting and artificial lighting design No specific requirement at product level		VISUAL COMFORT
Life Cycle Assessment	EPDs available		EPD [®]
Construction and Demolition Waste	Avoid sending waste to landfill No specific requirement at product level	RECYCLABLE	Ready



MILJÖBYGGNAD		MILJÖ BYGGNAD
CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
Indicator 13 (V3.0 & 3.1) Indicator 15 (V4.0)	Composition declared according to CLP/REACH None classified compounds are publicly declared if they make up >2% of composition	See available eBVD for Swedish adaptation
Indicator 14 (V3.0 & 3.1) Indicator 9 (V4.0)	Hazardous classified below CLP guidelines TVOC at 28 days ≤ 1000 µg/m3 Formaldehyde at 28 days ≤ 10 µg/m3	STOLUGING OPTIMAL INDOOR AIR QUALITY VIEWLA, HULDS, STOLUGE WEEKLA, HULDS, STOLUGE
Indicator 13 (V4.0)	At least 20% recycled content	See available eBVD for Swedish adaptation

The Green Building Card is used as a reference only for projects at design stage. This document by itself is not enough to validate the Green Building Certification requirements and manufacturer's documentation must be provided. In order to access the product certificates, please contact your TARKETT's sales representative.

